

UHF Narrow Band Multi Channel Transceiver STD-302Z 869MHz

The UHF FM narrow band semi-duplex radio module STD-302Z 869MHz is suitable for industrial remote control application and telemetry application operated in 869MHz ISM band. SAW filter and narrow band technique provides reliable data communication in industrial applications where interference rejection and practical distance range is required. Suitable for feedback systems.

Features

- 5mW RF power, 3.0V
- Programmable RF channel
- Receiver sensitivity -116dBm
- Excellent vibration and shock resistance / Mechanical durability
- FM narrow band
- 419, 429, 434, 447, 458 MHz available

Applications

- Industrial remote control system
- Telemetry system
- Data transmission



General

Parameter	Specification
Communication form	Half duplex
Frequency	868.025 to 870.975 MHz
Channel step	25 kHz Channel programmable (PLL IC:Fujitsu MB15E03)
Frequency stability	+/- 3.5 ppm (-20 to + 60 degree C)
Data rate	9,600 bps max (Pulse width min. 100 us, max 15 ms)
PLL reference frequency	21.25 MHz (TCXO)
PLL response	30 ms typ. (from PLL setting to LD out)
Supply voltage	3.0 to 5.5 V
Supply current	43 mA typ (TX) 28 mA typ (RX)
Operating temp. range	-20 to + 60 degree C (Storage : -30 to + 75 degree C)
TX/RX switching time	15 ms typ. (DI vs valid DO at the same frequency)
Dimension	30 X 50 X 9 mm
Weight	25g

Transmitter part


Parameter	Specification
Transmitter type	PLL synthesizer
RF output power	5 mW at 50 ohm
Deviation	+/- 2.75 kHz (PN9, 9600bps)
DI input level	L = GND, H = 3 V to Vcc
Residual FM noise	0.17 kHz

Receiver part

Parameter	Specification
Receiver type	Double superheterodyne
Receiver category	Category 1.5
IF	21.7 MHz (1st), 450 kHz (2nd)
Maximum input level	10 dBm
Receiver sensitivity	- 116 dBm (12 dB SINAD) - 113 dBm (BER 1%) - 107 dBm (0 error / 2556 bits)
Spurious response rejection	- 50 dBm (1st Mix, 2nd Mix)
Adjacent channel selectivity	- 50 dBm (+/- 25 kHz)
Adjacent channel saturation	- 20 dBm
Blocking	- 20 dBm
DO output level	L = GND, H = 2.8 V

Specifications are subject to change without prior notice

Interface



Interface voltage H = +2.8V, L=0V
Vcc and GND omitted for simplification