

Narrow band radio transceiver

STD-601 434 MHz

The STD-601 434 MHz is a miniature 434 MHz band transceiver designed for industrial remote control applications. This module conforms to the EN 300 220 standard.

The STD-601 434MHz has a simple serial interface and allows own communication protocol to be used. The RF Power, Data rate and Channel can be set through the use of dedicated serial commands.

Features

- Small 20 x 32 x 5 mm SMD
- Low current consumption
 - 26 mA (TX 10mW, 3V)
 - 19 mA (RX)
- Transparent interface for data input and output
- R&TTE (EN 300 220) compliance

Applications

- Industrial telecontrol
- Telemetry Systems



General

Parameter	Specification	Remark
Communication form	One Way, Half Duplex	
Emission class	F1D (2-GFSK)	
Supply voltage	3.0 to 5.0 V	
Guaranteed operating temp. range	-20 C to +65 C	
Maximum operating temp. range	-30 C to +75 C	
Frequency stability	+/- 3 ppm (-20 C to +65 C)	
Dimensions	20 x 32 x 5 mm	
Weight	4.5 g	

RF

Parameter	Specification	Remark
Frequency	433.0750 - 434.7750 MHz	
No. of channels	137 ch	
Data rate	4800 / 9600 bps	
TX current consumption	26 mA typ.	
RX current consumption	19 mA typ.	
Transmission power	10 / 5 / 1 mW	Nominal
Spurious emission (TX)	< -54 dBm (47 M - 74 M, 87.5 M - 118 M, 174 M - 230 M, 470 M - 862 MHz) < -37 dBm (Other frequencies below 1000 MHz) < -30 dBm (Frequencies above 1000 MHz)	
Adjacent CH leakage power(ACP)	< -37 dBm	(PN9-9600 bps) Ch25 kHz BW:16 kHz
Receiver sensitivity		
- 9600 bps	-113 dBm BER (1 % error)	PN9
- 4800 bps	-117 dBm BER (1 % error)	PN9
Adjacent channel selectivity	50 dB (+/-12.5 kHz) @ 4800 bps 50 dB (+/-25 kHz) @ 9600 bps	2 signal method, PN9, 1 % error 2 signal method, PN9, 1 % error
Spurious radiation (RX)	-57 dBm (below 1000 MHz) -47 dBm (above 1000 MHz)	
Blocking	70 dB	+/- 2 MHz, +/- 10 MHz

Timing

Parameter	Specification	Remark
Power on to TX/RX	350 ms typ.	
TX/RX switching time	10 ms typ.	

Interface

Parameter	Specification	Remark
Data Interface (DI / DO)	L=GND H=VCC, Asynchronous	Transparent inter face
Command interface (TXD / RXD)	UART 9600 / 19200 / 38400 bps, 8 data bit, No parity, 1 stop bit	

* Unless otherwise specified, specifications are typical values obtained under 9600 bps, 10 mW, 25 C, 434 MHz, 3 V
* Specifications are subject to change without prior notice