

Certification  
Issued Under the Authority of the  
Federal Communications Commission  
By:

Circuit Design, Inc.  
7557-1, Hotaka  
Azumino, Nagano, 399-8303  
Japan

Attention: Yukinaga Koike

UL Verification Services Inc.  
47173 Benicia Street  
Fremont, CA 94538

Date of Grant: 03/26/2024  
Application Dated: 03/26/2024

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is  
VALID ONLY for the equipment identified hereon for use under the Commission's  
Rules and Regulations listed below.

FCC IDENTIFIER: V9X-STD504  
Name of Grantee: Circuit Design, Inc.  
Equipment Class: Digital Transmission System  
Notes: 2.4 GHz DSSS low power radio transceiver  
Modular Type: Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	15C	2402.5 - 2476.5	0.0044		

Single Modular Approval. Output power listed is Conducted (Peak). Separate evaluation must be required for any portable configuration. When used in mobile applications, the module antenna(s) must be installed to meet the RF exposure compliance separation distance of 20 cm and any additional testing and authorization process as required. Compliance of this device in all final host configurations is the responsibility of the Grantee. The host integrator must follow the integration instructions provided by the module manufacturer and ensure that the composite-system end product complies with the FCC requirements by a technical assessment or evaluation to the FCC rules and to KDB Publication 996369. The host integrator is instructed to ensure that the end user has no manual instructions to remove or install the device. Co-location of this module with other transmitters that operate simultaneously are required to be evaluated using the FCC multi-transmitter procedures.