

**TCB****GRANT OF EQUIPMENT  
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the  
Federal Communications Commission****By:****UL Japan, Inc.  
4383-326 Asama-cho  
Ise-shi Mie, 5160021  
Japan****Date of Grant: 03/16/2015****Application Dated: 03/16/2015****Circuit Design, Inc.  
7557-1, Hotaka  
Azumino, Nagano, 399-8303  
Japan****Attention: Yukinaga Koike****NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

**FCC IDENTIFIER: V9X-STD503**  
**Name of Grantee: Circuit Design, Inc.**  
**Equipment Class: Digital Transmission System**  
**Notes: 2.4 GHz DSSS low power radio transceiver**  
**Modular Type: Single Modular**

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	15C	2402.5 - 2478.5	0.0047		

Single Modular approval. Output power listed is Conducted(Peak). Compliance of this device in all final host configurations is the responsibility of the Grantee. OEM integrators and end-users must be provided with specific operating instructions for satisfying RF exposure compliance. The antenna of this device must not be co-located or used in conjunction with any other antenna or transmitter except the conditions shown in this filing and/or in accordance with FCC multi-transmitter product guidelines. OEM integrators are instructed to ensure that the end user has no manual instructions to remove or install the device.

