

UHF Narrowband Multi Channel Transceiver STD-302Z 434 MHz

The UHF FM narrowband semi-duplex radio module STD-302Z 434 MHz is suitable for industrial remote control and telemetry applications operating in the 434 MHz ISM band. The SAW filter and narrowband technique provides reliable data communication in industrial applications where interference rejection and practical distance range is required. Suitable for feedback systems.

Features

- 10 mW RF power
- Programmable RF channel
- Receiver sensitivity -119 dBm
- Excellent vibration and shock resistance / Mechanical durability
- FSK narrowband
- CE marking
- 419 MHz (China) / 429 MHz (Japan) / 447 MHz (Korea) / 458 MHz (UK) / 869 MHz (EU) / 1216 MHz (Japan) / 1252 MHz (Japan) available

Applications

- Industrial remote control system
- Telemetry system
- Data transmission



General

Parameter	Specification
Applicable standard	EN 300 220
Communication method	Simplex, Half duplex
Emission type	F1D (FSK narrow)
Frequency	433.075 to 434.775 MHz
Channel step	25 kHz (Programmable)
Frequency stability	+/-3.5 ppm or less (-20 to +60 C)
RF bit rate	9,600 bps max (pulse width min. 100 us, max. 15 ms)
PLL reference frequency	21.25 MHz
PLL response	30 ms typ. (from PLL setting to LD out)
Supply voltage	3.0 to 5.5 V
Supply current	44 mA (TX), 28 mA (RX)
Operating temperature	-20 to +60 C
TX / RX switching time	15 ms typ. (DI vs valid DO at the same frequency)
Dimensions	30 x 50 x 9 mm
Weight	25 g

Transmitter part

Parameter	Specification
Oscillation system	PLL controlled VCO
RF output power	10 mW at 50 ohm
Deviation	+/-2.75 kHz (PN9 9,600 bps)
Data input	Digital L = GND, H = 3 V to Vcc
Spurious emission	< -54 dBm (47 to 74, 87.5 to 118, 174 to 230, 470 to 790 MHz) < -36 dBm (Frequencies below 1000 MHz) < -30 dBm (Frequencies above 1000 MHz)
Adjacent channel leakage power	< -37 dBm (CH 25 kHz, BW 17.5 kHz, PN9 9,600 bps)

Receiver part

Parameter	Specification
Receiver type	Double superheterodyne
Receiver category	1.5
IF frequency	21.7 MHz (1st), 450 kHz (2nd)
Maximum input level	+10 dBm
Sensitivity (12 dB SINAD)	-119 dBm
Sensitivity (BER 1%)	-116 dBm (PN9 9,600 bps)
Blocking	> -20 dBm (+/-10 MHz), > -25 dBm (+/-2 MHz)
Data output	Digital L = GND, H = 2.8 V
Adjacent channel selectivity	> -50 dBm (+/-25 kHz)

Specifications are subject to change without prior notice